



Specifications Sylvania LED Downlight Insaver Slim 225 Aluminium White 41W 4800lm 70D - 830 Warm White | Cutout 225mm - IP44 - Dimmable



[View Product](#)

General Information

| | |
|--------------------------|------------------------------|
| SKU | 255250 |
| EAN | 5410288305400 |
| Brand | Sylvania |
| Manufacturer Name | INSV SL IP44 DL 225 4800 830 |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|--------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Beam Angle (degree) | 70 |
| Luminous Efficacy (lm/W) | 117.1 |

| | |
|-----------------------|--------------------------|
| Power factor | >0.95 |
| Unified Glare Rating | < 22 - for general areas |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 225 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK07 - 2 joules |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector] |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 60 |
| Diameter (mm) | 240 |

Sensor Information

| | |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process